## FRONT VIEW Break Away Curtain Track Smooth 12" Aluminum Back Wall Anti-Ligature Grab Bar Feature Line Aluminum Anti-Ligature Grab Bar $82\frac{7}{8}$ " Molded Seat 34<del>/</del> 30/2 18<del>/</del> <u>-7</u> 8 $41\frac{1}{4}$ SIDE VIEW TOP VIEW 82<del>7</del>" Feature 20% Line Slip Resistant

Surface

Factory Installed

6" Minimum Core Around Drain Plus 1/2" Deep × 10" Diameter Recess

EasyBase™

EasyBase™

Acrylic Floor

*Pulmmmm* 

Steel Stiffener

CROSS SECTION OF THRESHOLD

7/8"

Coordinate Finished Floor Height For Code

Finished Floor May Be

No More Than 1/4"

Below The Top Of

Compartment

Threshold.



## SPECIFICATION SHEET

This shower enclosure shall be model XSA 4136 BF .875 right, or left. Finished surface shall be of a sanitary grade cast acrylic exhibiting a minimal thickness of 15 dry mils and a finished cured Barcoal hardness of 80-90 as tested with ASTM D-2583. Unit construction shall be of a molded reinforced fiberglass with a 15% minimum fiberglass content.

The unit shall have outside dimensions of 41 I/4"  $\times$  36 I/4"  $\times$  82 7/8". The unit shall meet ANSI Z124.1-2. CSA-B45.5, ANSI A117.1, ADA, and Home Innovation Research Lab.

The enclosure shall be equipped with the following accessories: I) One  $12" \times 1 \text{ I}/2"$  diameter aluminum anti-ligarure grab bar on the back wall, 2) One  $28" \times 1 \text{ I}/2"$  diameter aluminum anti ligature grab bar on the valve wall, both with I I/2" statute clearance, secured from the rear with stainless steel bolts and  $3" \times 3" \times 11$  gauge metal mounting plates, 3) Large molded seat,

- 4) Molded soap ledge, 5) Break away curtain track,
- 6) EasyBase™ self sustaining bottom, 8) 7/8" threshold.

THIS UNIT FEATURES THE OUTSIDE DIMENSION OF 41 1/4" OF OVERALL WIDTH, THIS DOES NOT ALLOW FOR FULL ENCLOSURE OF THE BOLTS AND NUTS USED TO SECURE THE BARS AND SEAT IN PLACE. THE BOLT AND NUT COMBINATION SHOULD NOT PROTRUDE MORE THAN 3/4" ON EITHER SIDE OF THE SHOWER WALLS. THIS MAY REQUIRE THE NEED TO NOTCH STUDS TO ALOW BOLT CLEARANCE FOR A DRYWALL ENCLOSED FIRE WALL INSTALLATION, ADJUSTMENT OF THE WALL BOARD MAY BE NECESSARY TO PROVIDE CLEARANCE OF THE BOLT(S) WHILE MAINTAINING THE INTEGRITY OF THE DRYWALL ENCLOSED FIRE WALL ENCLOSED FIRE WALL ENCLOSED FIRE WALL ENCLOSED FIRE WALL ENCLOSURE.

NOTE: THIS UNIT WILL NOT ACCEPT A DOOR.

Job Name	Approved By Name Dat		Dete	COMFORT DESIGNS	
Job Name	Approved by	Name	Date	CONFORT DESIGNS	
Project No	Architect			Model No. XSA 4136 BF .875 Correctional	
Comfort Designs 435 Industrial Road Savannah, TN 38372 tel 800.443.7269	Engineer			Drawing No. XSA 4136 BF .875 AlmAnti-LigHBW AlmAnti-LigHSW MS BRK EB	
	Rep			Date Issued. 4-6-12	Drawing Rev. 7-6-20
	Wholesaler			Material. Cast acrylic	
	Comments			Color.	
fax 73 I.925.4290 www.comfortdesignsbathware.com				Dimensions are in inches. Due to the nature of the materials dimensions may vary $\pm$ 1/2"	

Center of Drain