



SUBMITTAL

This shower enclosure shall be model SSS 3636 SH 4.0, right, or left. Finished surface shall be of a sanitary grade Solid Surface exhibiting a minimal thickness of 55 dry mils and a finished cured Barcoal hardness of 80-90 as tested with ASTM D-2583. Unit construction shall be of a molded reinforced fiberglass with a 15% minimum fiberglass content.

HANDED BY THE CENTER

The unit shall have outside dimensions of 35 3/4" x 36" x 77 1/4". The unit shall meet CSA B45.5-11, BOCA, UPC, Home Innovation Research Lab, IAPMOZ124-2011, and shall meet the requirements of the Southern Building Code.

The enclosure shall be equipped with the following accessories:

- 1) One inch diameter stainless steel curtain rod with receiver cups,
- 2) Molded soap ledges in both corners,
- 3) Molded lower ledge on the back wall,
- 4) Solid surface finish,
- 5) Center drain location,
- 6) 4" Threshold.

THIS UNIT FEATURES THE OUTSIDE DIMENSION OF 35 3/4" OF OVERALL WIDTH. THIS DOES NOT ALLOW FOR FULL ENCLOSURE OF THE BOLTS AND NUTS USED TO SECURE THE BARS AND SEAT IN PLACE. THE BOLT AND NUT COMBINATION SHOULD NOT PROTRUDE MORE THAN 3/4" ON EITHER SIDE OF THE SHOWER WALLS. THIS MAY REQUIRE THE NEED TO NOTCH STUDS TO ALLOW BOLT CLEARANCE FOR A DRYWALL ENCLOSED FIRE WALL INSTALLATION. ADJUSTMENT OF THE WALL BOARD MAY BE NECESSARY TO PROVIDE CLEARANCE OF THE BOLT(S) WHILE MAINTAINING THE INTEGRITY OF THE DRYWALL ENCLOSED FIRE WALL ENCLOSURE.

Job Name	Approved By Print Name	Date	COMFORT DESIGNS	
Project No	Approved By Signature		Model No. SSS 3636 SH 4.0-I	
Comfort Designs 435 Industrial Road Savannah, TN 38372 tel 800.443.7269 fax 731.925.4290 www.comfortdesignsbathware.com	Architect		Drawing No. SSS 3636 SH 4.0 CR	
	Engineer		Date Issued. 2-28-13	Drawing Rev. 5-28-14
	Rep		Material. Solid Surface	
	Wholesaler		Color.	
	Comments			Dimensions are in inches. Due to the nature of the materials dimensions may vary ± 1/2"