



## SUBMITTAL

This shower enclosure shall be model XSS 3636 SH 4.0 center. Finished surface shall be of a sanitary grade applied acrylic. The base shall be attached to the sump in such manner to form an integral part with an inner and outer coating of polyester resin. Unit construction shall be of a molded reinforced fiberglass with a 15% minimum fiberglass content.

The unit shall have outside dimensions of 35 3/4" x 37 1/4" x 77 1/2". The unit shall meet CSA B45.5-11, HUD-UM73, and Home Innovation Research Lab.

## HANDED BY THE CENTER

The enclosure shall be equipped with the following accessories:

- 1) Molded leg ledge,
- 2) Molded soap ledges,
- 3) Center drain location,
- 4) 4.0" Threshold.

THIS UNIT FEATURES THE OUTSIDE DIMENSION OF 35 3/4" OF OVERALL WIDTH. THIS DOES NOT ALLOW FOR FULL ENCLOSURE OF THE BOLTS AND NUTS USED TO SECURE THE BARS AND SEAT IN PLACE. THE BOLT AND NUT COMBINATION SHOULD NOT PROTRUDE MORE THAN 3/4" ON EITHER SIDE OF THE SHOWER WALLS. THIS MAY REQUIRE THE NEED TO NOTCH STUDS TO ALLOW BOLT CLEARANCE FOR A DRYWALL ENCLOSED FIRE WALL INSTALLATION. ADJUSTMENT OF THE WALL BOARD MAY BE NECESSARY TO PROVIDE CLEARANCE OF THE BOLT(S) WHILE MAINTAINING THE INTEGRITY OF THE DRYWALL ENCLOSED FIRE WALL ENCLOSURE.

Job Name	Approved By Print Name	Date	<b>COMFORT DESIGNS</b>	
Project No	Approved By Signature		Model No. XSS 3636 SH 4,0-1	
Comfort Designs 435 Industrial Road Savannah, TN 38372 tel 800.443.7269 fax 731.925.4290 www.comfortdesignsbathware.com	Architect		Drawing No. XSS 3636 SH 4.0	
	Engineer		Date Issued. 4-3-12	Drawing Rev. 12-1-16
	Rep		Material, Acrylic Surface	
	Wholesaler		Color,	
	Comments			Dimensions are in inches. Due to the nature of the materials dimensions may vary ± 1/2"