


CROSS SECTION OF THRESHOLD





SUBMITTAL

This shower enclosure shall be model XST 5038 TR .75 left or right. Finished surface shall be of a sanitary grade applied acrylic. The base shall be attached to the sump in such manner to form an integral part with an inner and outer coating of polyester resin. Unit construction shall be of a molded reinforced fiberglass with a 15% minimum fiberglass content.

The unit shall have outside dimensions of 50 5/8" \times 38 1/2" \times 79". The unit shall meet CSA B45.5-11, HUD-UM73, and Home Innovation Research Lab.

HANDED BY THE VALVE

The enclosure shall be equipped with the following accessories:

I) One 22" \times I I/4" diameter I8 gauge white grab bar horizontal on the back wall, 2) One 24" \times I I/4" diameter white grab bar horizontal on the side wall, both with I I/2" statute clearance, secured from the rear with stainless steel bolts, and 3" \times 3" \times II gauge metal mounting plate, 3) 32" \times 21" frameless white HDPE fold up seat, 4) One inch diameter white curtain rod with receiver cups, 5) Molded ledge low on the back wall, 6) Subway tile pattern, 7) Tri-Cell backing, 8) Integral front trench drain, 9) Factory installed Easy Base self sustaining bottom, 10) 3/4" threshold.

THIS UNIT FEATURES THE OUTSIDE DIMENSION OF 50 5/8" OF OVERALL WIDTH. THIS DOES NOT ALLOW FOR FULL ENCLOSURE OF THE BOLTS AND NUTS USED TO SECURE THE BARS AND SEAT IN PLACE. THE BOLT AND NUT COMBINATION SHOULD NOT PROTRUDE MORE THAN 3/4" ON EITHER SIDE OF THE SHOWER WALLS. THIS MAY REQUIRE THE NEED TO NOTCH STUDS TO ALLOW BOLT CLEARANCE FORA DRYWALL ENCLOSED FIRE WALL INSTALLATION. ADJUSTMENT OF THE WALL BOARD MAY BE NECESSARY TO PROVIDE CLEARANCE OF THE BOLT(S) WHILE MAINTAINING THE INTEGRITY OF THE DRYWALL ENCLOSED FIRE WALL ENCLOSED FIRE WALL ENCLOSED FIRE WALL ENCLOSED FIRE WALL ENCLOSED FIRE WALL

NOTE: THIS UNIT WILL NOT ACCEPT A DOOR.

The Large With Decards					
Job Name	Approved By Print Name		Date	COMFORT DESIGNS	
Project No	Approved By Signature			Model No. XST 5038 TR .75	
Comfort Designs 435 Industrial Road Savannah, TN 38372 tel 800.443.7269 fax 731.925.4290 www.comfortdesignsbathware.com	Architect			Drawing No. XST 5038 TR .75 WHBW WHSW FHDP WCR Tri-Cell Easy Base	
	Engineer			Date Issued. 8-7-12	Drawing Rev. 12-7-16
	Rep			Material, Acrylic Surface	
	Wholesaler			Color,	
	Comments			Dimensions are in inches. Due to the nature of the materials dimensions may vary \pm 1/2"	